


Tonmind SIP PCB Board SIP-K20C-M

1. Two-way intercom communication
2. Support 48K OPUS Audio Codec
3. SIP & ONVIF protocol compatibility
4. Pre-recorded message(WAV/MP3)
5. Alarm: GPIO, HTTP URL
6. MIC and speaker interface
7. Reset and volume control
8. FHD 1080P Video input



Specification:

Video Input	FHD 1080P@30fps
Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Audio Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Network Interface	RJ45, 10BASE-T/100BASE-TX
Interface	1*MIC input, 1* Speaker output, 2* IO Alarm input, 1* Reset
Power	PoE or DC 12V
Rated Power	15W
Operating Temperature	-30°C — +60°C
Operating Humidity	5%-85%
Function	Compatible with VoIP devices and ONVIF VMS, support two way communication, pre-recorded messages, schedule play, GPIO in, HTTP control
Application	Speaker, Intercom / Door Phone
Size	65mm * 52mm * 27mm
Others	Support Web Browser Settings, Firmware Upgrade